480057 - Hazelnut Concentrated Stain 057

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: 480057 - Hazelnut Concentrated Stain 057

Other means of identification:

UFI: X690-204J-Q007-MNCJ

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Wood stain. For professional users/industrial user only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Valresa Coatings, S.A.
Pol. Ind. Reva S-13 Avda. dels Gremis s/n
46190 Riba-roja de Turia Valencia - Spain
Phone: +34 961669560
www.valresa.com

1.4 Emergency telephone number: +34 961669560 (Only available during office hours)

SECTION 2: HAZARDS IDENTIFICATION **

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Eye Irrit. 2: Eye irritation, Category 2, H319
Flam. Liq. 2: Flammable liquids, Category 2, H225
Skin Sens. 1: Sensitisation, skin, Category 1, H317
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger



Hazard statements:

Causes serious eye irritation.
Highly flammable liquid and vapour.
May cause an allergic skin reaction.
May cause drowsiness or dizziness.

Precautionary statements:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
In case of fire: Use ABC powder extinguisher to extinguish.
Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Supplementary information:

Repeated exposure may cause skin dryness or cracking.
Contains C.I.Acid Black 172.

Substances that contribute to the classification

1-methoxy-2-propanol; propan-2-ol; acetone; Sodium bis[2-[[5-(aminosulphonyl)-2-hydroxyphenyl]azo]-3-oxo-N-phenylbutyramidato(2-)]cobaltate(1-)

Authorized substances:

Acid Black 164 - Reaction products of diazotised 4-amino-3-hydroxy-7-nitronaphthalene-1-sulfonic acid coupled with 2-naphthol and 2-amino-4 (or 5)-nitrophenol, chelated with chromium (3+), sodium salts (01-2120060617-55-XXXX)

UFI: X690-204J-Q007-MNCJ

*** Changes with regards to the previous version*

- CONTINUED ON NEXT PAGE -

SECTION 2: HAZARDS IDENTIFICATION ** (continued)

2.3 Other hazards:

Product does not meet PBT/vPvB criteria
Endocrine-disrupting properties: The product does not meet the criteria.

*** Changes with regards to the previous version*

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of colourants in solvents

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 107-98-2 EC: 203-539-1 Index: 603-064-00-3 REACH: 01-2119457435-35-XXXX	**1-methoxy-2-propanol**(1)	ATP ATP01	**25 - <50 %**
	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336 - Warning	
CAS: 67-63-0 EC: 200-661-7 Index: 603-117-00-0 REACH: 01-2119457558-25-XXXX	**propan-2-ol**(1)	ATP CLP00	**25 - <50 %**
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger	
CAS: 67-64-1 EC: 200-662-2 Index: 606-001-00-8 REACH: 01-2119471330-49-XXXX	**acetone**(1)	ATP CLP00	**10 - <25 %**
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	
CAS: 112-34-5 EC: 203-961-6 Index: 603-096-00-8 REACH: 01-2119475104-44-XXXX	**2-(2-butoxyethoxy)ethanol**(1)	ATP CLP00	**2,5 - <5 %**
	Regulation 1272/2008	Eye Irrit. 2: H319 - Warning	
CAS: 72496-88-9 EC: 276-701-2 Index: Non-applicable REACH: 01-2120071400-71-XXXX	**Sodium bis[2-[[5-(aminosulphonyl)-2-hydroxyphenyl]azo]-3-oxo-N-phenylbutyramidato(2-)]cobaltate(1-)**(1)	Self-classified	**2,5 - <5 %**
	Regulation 1272/2008	Aquatic Chronic 3: H412; Skin Sens. 1: H317 - Warning	
CAS: 57693-14-8 EC: 260-906-9 Index: Non-applicable REACH: 01-2119969289-17-XXXX	**C.I.Acid Black 172**(1)	Self-classified	**0,25 - <1 %**
	Regulation 1272/2008	Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Sens. 1: H317 - Warning	
CAS: Non-applicable EC: 941-684-9 Index: Non-applicable REACH: Non-applicable	**Acid Black 164 - Reaction products of diazotised 4-amino-3-hydroxy-7-nitronaphthalene-1-sulfonic acid coupled with 2-naphthol and 2-amino-4 (or 5)-nitrophenol, chelated with chromium (3+), sodium salts**(1)	Self-classified	**<0,25 %**
	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410 - Warning	

(1) Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

- CONTINUED ON NEXT PAGE -

SECTION 4: FIRST AID MEASURES (continued)

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

In case of consumption, seek immediate medical assistance showing the SDS for the product.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO_2).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

It is recommended to avoid environmental spillage of both the product and its container.

6.3 Methods and material for containment and cleaning up:

It is recommended:

- CONTINUED ON NEXT PAGE -

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 ºC

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC,Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
1-methoxy-2-propanol	IOELV (8h)	100 ppm	375 mg/m³
CAS: 107-98-2 EC: 203-539-1	IOELV (STEL)	150 ppm	568 mg/m³
2-(2-butoxyethoxy)ethanol	IOELV (8h)	10 ppm	67,5 mg/m³
CAS: 112-34-5 EC: 203-961-6	IOELV (STEL)	15 ppm	101,2 mg/m³
acetone	IOELV (8h)	500 ppm	1210 mg/m³
CAS: 67-64-1 EC: 200-662-2	IOELV (STEL)		

DNEL (Workers):

- CONTINUED ON NEXT PAGE -

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
1-methoxy-2-propanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 107-98-2	Dermal	Non-applicable	Non-applicable	183 mg/kg	Non-applicable
EC: 203-539-1	Inhalation	553,5 mg/m³	553,5 mg/m³	369 mg/m³	Non-applicable
propan-2-ol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 67-63-0	Dermal	Non-applicable	Non-applicable	888 mg/kg	Non-applicable
EC: 200-661-7	Inhalation	Non-applicable	Non-applicable	500 mg/m³	Non-applicable
acetone	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 67-64-1	Dermal	Non-applicable	Non-applicable	186 mg/kg	Non-applicable
EC: 200-662-2	Inhalation	Non-applicable	2420 mg/m³	1210 mg/m³	Non-applicable
2-(2-butoxyethoxy)ethanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 112-34-5	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
EC: 203-961-6	Inhalation	Non-applicable	101,2 mg/m³	67,5 mg/m³	67,5 mg/m³
C.I.Acid Black 172	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 57693-14-8	Dermal	Non-applicable	Non-applicable	27,78 mg/kg	Non-applicable
EC: 260-906-9	Inhalation	24,5 mg/m³	Non-applicable	24,5 mg/m³	Non-applicable

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
1-methoxy-2-propanol	Oral	Non-applicable	Non-applicable	33 mg/kg	Non-applicable
CAS: 107-98-2	Dermal	Non-applicable	Non-applicable	78 mg/kg	Non-applicable
EC: 203-539-1	Inhalation	Non-applicable	Non-applicable	43,9 mg/m³	Non-applicable
propan-2-ol	Oral	Non-applicable	Non-applicable	26 mg/kg	Non-applicable
CAS: 67-63-0	Dermal	Non-applicable	Non-applicable	319 mg/kg	Non-applicable
EC: 200-661-7	Inhalation	Non-applicable	Non-applicable	89 mg/m³	Non-applicable
acetone	Oral	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
CAS: 67-64-1	Dermal	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
EC: 200-662-2	Inhalation	Non-applicable	Non-applicable	200 mg/m³	Non-applicable
2-(2-butoxyethoxy)ethanol	Oral	Non-applicable	Non-applicable	5 mg/kg	Non-applicable
CAS: 112-34-5	Dermal	Non-applicable	Non-applicable	50 mg/kg	Non-applicable
EC: 203-961-6	Inhalation	Non-applicable	60,7 mg/m³	40,5 mg/m³	40,5 mg/m³
C.I.Acid Black 172	Oral	Non-applicable	Non-applicable	8,33 mg/kg	Non-applicable
CAS: 57693-14-8	Dermal	Non-applicable	Non-applicable	16,7 mg/kg	Non-applicable
EC: 260-906-9	Inhalation	Non-applicable	Non-applicable	14,7 mg/m³	Non-applicable

PNEC:

Identification				
1-methoxy-2-propanol	STP	100 mg/L	Fresh water	10 mg/L
CAS: 107-98-2	Soil	4,59 mg/kg	Marine water	1 mg/L
EC: 203-539-1	Intermittent	100 mg/L	Sediment (Fresh water)	52,3 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	5,2 mg/kg
propan-2-ol	STP	2251 mg/L	Fresh water	140,9 mg/L
CAS: 67-63-0	Soil	28 mg/kg	Marine water	140,9 mg/L
EC: 200-661-7	Intermittent	140,9 mg/L	Sediment (Fresh water)	552 mg/kg
	Oral	0,16 g/kg	Sediment (Marine water)	552 mg/kg
acetone	STP	100 mg/L	Fresh water	10,6 mg/L
CAS: 67-64-1	Soil	29,5 mg/kg	Marine water	1,06 mg/L
EC: 200-662-2	Intermittent	21 mg/L	Sediment (Fresh water)	30,4 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	3,04 mg/kg
2-(2-butoxyethoxy)ethanol	STP	200 mg/L	Fresh water	1,1 mg/L
CAS: 112-34-5	Soil	0,32 mg/kg	Marine water	0,11 mg/L
EC: 203-961-6	Intermittent	11 mg/L	Sediment (Fresh water)	4,4 mg/kg
	Oral	0,056 g/kg	Sediment (Marine water)	0,44 mg/kg

- CONTINUED ON NEXT PAGE -

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
C.I.Acid Black 172	STP	0,781 mg/L	Fresh water	0,003 mg/L
CAS: 57693-14-8	Soil	600 mg/kg	Marine water	0,0003 mg/L
EC: 260-906-9	Intermittent	0,03 mg/L	Sediment (Fresh water)	3000 mg/kg
	Oral	0,0333 g/kg	Sediment (Marine water)	300 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases, vapours and particles	CE CAT III	EN 149:2001+A1:2009 EN 405:2002+A1:2010 EN ISO 136:1998	Replace when an increase in resistence to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)	CE CAT III	EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield	CE CAT II	EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer´s instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	CE CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer´s instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	CE CAT III	EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

- CONTINUED ON NEXT PAGE -

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	85,06 % weight
V.O.C. density at 25 ºC:	737,67 kg/m³ (737,67 g/L)
Average carbon number:	3,38
Average molecular weight:	70,84 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 ºC:	Liquid
Appearance:	Not available
Colour:	Brown
Odour:	Not available
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	85 ºC
Vapour pressure at 25 ºC:	12506 Pa
Vapour pressure at 50 ºC:	36760,13 Pa (36,76 kPa)
Evaporation rate at 25 ºC:	Non-applicable *

Product description:

Density at 25 ºC:	867,3 kg/m³
Relative density at 25 ºC:	0,867
Dynamic viscosity at 25 ºC:	Non-applicable *
Kinematic viscosity at 25 ºC:	Non-applicable *
Kinematic viscosity at 40 ºC:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 25 ºC:	Non-applicable *
Partition coefficient n-octanol/water 25 ºC:	Non-applicable *
Solubility in water at 25 ºC:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *

Flammability:

Flash Point:	8 ºC
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	204 ºC
Lower flammability limit:	Not available
Upper flammability limit:	Not available

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Particle characteristics:

Median equivalent diameter:	Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

Other safety characteristics:

Surface tension at 25 ºC:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO_2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- CONTINUED ON NEXT PAGE -

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
  IARC: Sodium bis[2-[[5-(aminosulphonyl)-2-hydroxyphenyl]azo]-3-oxo-N-phenylbutyramidato(2-)]cobaltate(1-) (2B); propan-2-ol (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Repeated exposure may cause skin dryness or cracking

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Sodium bis[2-[[5-(aminosulphonyl)-2-hydroxyphenyl]azo]-3-oxo-N-phenylbutyramidato(2-)]cobaltate(1-)	LD50 oral	10000 mg/kg	Rat
CAS: 72496-88-9	LD50 dermal	>2000 mg/kg	
EC: 276-701-2	LC50 inhalation	>5 mg/L	
1-methoxy-2-propanol	LD50 oral	>2000 mg/kg	
CAS: 107-98-2	LD50 dermal	>2000 mg/kg	
EC: 203-539-1	LC50 inhalation	>20 mg/L	
2-(2-butoxyethoxy)ethanol	LD50 oral	>2000 mg/kg	
CAS: 112-34-5	LD50 dermal	>2000 mg/kg	
EC: 203-961-6	LC50 inhalation	>20 mg/L	
propan-2-ol	LD50 oral	5280 mg/kg	Rat
CAS: 67-63-0	LD50 dermal	12800 mg/kg	Rat
EC: 200-661-7	LC50 inhalation	72,6 mg/L (4 h)	Rat
acetone	LD50 oral	5800 mg/kg	Rat
CAS: 67-64-1	LD50 dermal	7426 mg/kg	Rabbit
EC: 200-662-2	LC50 inhalation	76 mg/L (4 h)	Rat

- CONTINUED ON NEXT PAGE -

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	Acute toxicity		Genus
C.I.Acid Black 172	LD50 oral	>2000 mg/kg	
CAS: 57693-14-8	LD50 dermal	>2000 mg/kg	
EC: 260-906-9	LC50 inhalation	>5 mg/L	
Acid Black 164 - Reaction products of diazotised 4-amino-3-hydroxy-7-nitronaphthalene-1-sulfonic acid coupled with 2-naphthol and 2-amino-4 (or 5)-nitrophenol, chelated with chromium (3+), sodium salts	LD50 oral	>2000 mg/kg	
CAS: Non-applicable	LD50 dermal	>2000 mg/kg	
EC: 941-684-9	LC50 inhalation	Non-applicable	

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
1-methoxy-2-propanol	LC50	20800 mg/L (96 h)	Pimephales promelas	Fish
CAS: 107-98-2	EC50	23300 mg/L (48 h)	Daphnia magna	Crustacean
EC: 203-539-1	EC50	1000 mg/L (168 h)	Selenastrum capricornutum	Algae
propan-2-ol	LC50	9640 mg/L (96 h)	Pimephales promelas	Fish
CAS: 67-63-0	EC50	13299 mg/L (48 h)	Daphnia magna	Crustacean
EC: 200-661-7	EC50	1000 mg/L (72 h)	Scenedesmus subspicatus	Algae
acetone	LC50	5540 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 67-64-1	EC50	8800 mg/L (48 h)	Daphnia pulex	Crustacean
EC: 200-662-2	EC50	3400 mg/L (48 h)	Chlorella pyrenoidosa	Algae
2-(2-butoxyethoxy)ethanol	LC50	1300 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 112-34-5	EC50	2850 mg/L (24 h)	Daphnia magna	Crustacean
EC: 203-961-6	EC50	53 mg/L (192 h)	Microcystis aeruginosa	Algae
Sodium bis[2-[[5-(aminosulphonyl)-2-hydroxyphenyl]azo]-3-oxo-N-phenylbutyramidato(2-)]cobaltate(1-)	LC50	42 mg/L (96 h)	Brachydanio rerio	Fish
CAS: 72496-88-9	EC50	55 mg/L (48 h)	Daphnia magna	Crustacean
EC: 276-701-2	EC50	32 mg/L (96 h)	Scenedesmus subspicatus	Algae
C.I.Acid Black 172	LC50	3 mg/L (96 h)	N/A	Fish
CAS: 57693-14-8	EC50	79 mg/L (48 h)	Daphnia magna	Crustacean
EC: 260-906-9	EC50	Non-applicable		
Acid Black 164 - Reaction products of diazotised 4-amino-3-hydroxy-7-nitronaphthalene-1-sulfonic acid coupled with 2-naphthol and 2-amino-4 (or 5)-nitrophenol, chelated with chromium (3+), sodium salts	LC50	>0.1 - 1 mg/L (96 h)		Fish
CAS: Non-applicable	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
EC: 941-684-9	EC50	>0.1 - 1 mg/L (72 h)		Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
acetone	NOEC	Non-applicable		
CAS: 67-64-1 EC: 200-662-2	NOEC	2212 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

- CONTINUED ON NEXT PAGE -

SECTION 12: ECOLOGICAL INFORMATION (continued)

Substance-specific information:

Identification	Degradability		Biodegradability	
1-methoxy-2-propanol	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 107-98-2	COD	Non-applicable	Period	28 days
EC: 203-539-1	BOD5/COD	Non-applicable	% Biodegradable	90 %
propan-2-ol	BOD5	1,19 g O2/g	Concentration	100 mg/L
CAS: 67-63-0	COD	2,23 g O2/g	Period	14 days
EC: 200-661-7	BOD5/COD	0,53	% Biodegradable	86 %
acetone	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 67-64-1	COD	Non-applicable	Period	28 days
EC: 200-662-2	BOD5/COD	Non-applicable	% Biodegradable	96 %
2-(2-butoxyethoxy)ethanol	BOD5	0,25 g O2/g	Concentration	100 mg/L
CAS: 112-34-5	COD	2,08 g O2/g	Period	28 days
EC: 203-961-6	BOD5/COD	0,12	% Biodegradable	92 %
C.I.Acid Black 172	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 57693-14-8	COD	Non-applicable	Period	28 days
EC: 260-906-9	BOD5/COD	Non-applicable	% Biodegradable	68 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
1-methoxy-2-propanol	BCF	3
CAS: 107-98-2	Pow Log	-0.44
EC: 203-539-1	Potential	Low
propan-2-ol	BCF	3
CAS: 67-63-0	Pow Log	0.05
EC: 200-661-7	Potential	Low
acetone	BCF	1
CAS: 67-64-1	Pow Log	-0.24
EC: 200-662-2	Potential	Low
2-(2-butoxyethoxy)ethanol	BCF	0.46
CAS: 112-34-5	Pow Log	0.56
EC: 203-961-6	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
propan-2-ol	Koc	1.5	Henry	8,207E-1 Pa·m³/mol
CAS: 67-63-0	Conclusion	Very High	Dry soil	Yes
EC: 200-661-7	Surface tension	2,24E-2 N/m (25 ºC)	Moist soil	Yes
acetone	Koc	1	Henry	2,93 Pa·m³/mol
CAS: 67-64-1	Conclusion	Very High	Dry soil	Yes
EC: 200-662-2	Surface tension	2,304E-2 N/m (25 ºC)	Moist soil	Yes
2-(2-butoxyethoxy)ethanol	Koc	48	Henry	7,2E-9 Pa·m³/mol
CAS: 112-34-5	Conclusion	Very High	Dry soil	No
EC: 203-961-6	Surface tension	3,395E-2 N/m (25 ºC)	Moist soil	No

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

- CONTINUED ON NEXT PAGE -

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:



14.1	**UN number or ID number:**	UN1263
14.2	**UN proper shipping name:**	PAINT
14.3	**Transport hazard class(es):**	3
	Labels:	3
14.4	**Packing group:**	II
14.5	**Environmental hazards:**	No
14.6	**Special precautions for user**	
	Special regulations:	163, 367, 640D, 650
	Tunnel restriction code:	D/E
	Physico-Chemical properties:	see section 9
	Limited quantities:	5 L
14.7	**Maritime transport in bulk according to IMO instruments:**	Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 40-20:



14.1	**UN number or ID number:**	UN1263
14.2	**UN proper shipping name:**	PAINT
14.3	**Transport hazard class(es):**	3
	Labels:	3
14.4	**Packing group:**	II
14.5	**Marine pollutant:**	No
14.6	**Special precautions for user**	
	Special regulations:	367, 163
	EmS Codes:	F-E, S-E
	Physico-Chemical properties:	see section 9
	Limited quantities:	5 L
	Segregation group:	Non-applicable
14.7	**Maritime transport in bulk according to IMO instruments:**	Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2023:

- CONTINUED ON NEXT PAGE -

SECTION 14: TRANSPORT INFORMATION (continued)



14.1	**UN number or ID number:**	UN1263
14.2	**UN proper shipping name:**	PAINT
14.3	**Transport hazard class(es):**	3
	Labels:	3
14.4	**Packing group:**	II
14.5	**Environmental hazards:**	No
14.6	**Special precautions for user**	
	Physico-Chemical properties:	see section 9
14.7	**Maritime transport in bulk according to IMO instruments:**	Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: propan-2-ol (Product-type 1, 2, 4)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Contains more than 3 % of 2-(2-butoxyethoxy)ethanol by weight. 1. Shall not be placed on the market for the first time after 27 June 2010, for supply to the general public, as a constituent of spray paints or spray cleaners in aerosol dispensers in concentrations equal to or greater than 3 % by weight. 2. Spray paints and spray cleaners in aerosol dispensers containing DEGBE and not conforming to paragraph 1 shall not be placed on the market for supply to the general public after 27 December 2010. 3. Without prejudice to other Community legislation concerning the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that paints other than spray paints containing DEGBE in concentrations equal to or greater than 3 % by weight of that are placed on the market for supply to the general public are visibly, legibly and indelibly marked by 27 December 2010 as follows: 'Do not use in paint spraying equipment'.
Regulation (EU) 2019/1148 on the marketing and use of explosives precursors: Contains acetone. Product under the provisions of Article 9. However, products that contain explosives precursors only to such a small extent and in such complex mixtures that the extraction of the explosives precursors is technically extremely difficult should be excluded from the scope of this Regulation.
Shall not be used in:
—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
—tricks and jokes,
—games for one or more participants, or any article intended to be used as such, even with ornamental aspects.
Contains C.I.Acid Brown 355. Azodyes which, by reductive cleavage of one or more azo groups, may release one or more of the aromatic amines listed in Appendix 8, in detectable concentrations, i.e. above 30 mg/kg (0,003 % by weight) in the articles or in the dyed parts thereof, according to the testing methods listed in Appendix 10, shall not be used, in textile and leather articles which may come into direct and prolonged contact with the human skin or oral cavity, such as:
— clothing, bedding, towels, hairpieces, wigs, hats, nappies and other sanitary items, sleeping bags,
— footwear, gloves, wristwatch straps, handbags, purses/wallets, briefcases, chair covers, purses worn round the neck,
— textile or leather toys and toys which include textile or leather garments,
— yarn and fabrics intended for use by the final consumer.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

- CONTINUED ON NEXT PAGE -

SECTION 15: REGULATORY INFORMATION (continued)

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Precautionary statements

Texts of the legislative phrases mentioned in section 2:

H317: May cause an allergic skin reaction.
H336: May cause drowsiness or dizziness.
H225: Highly flammable liquid and vapour.
H319: Causes serious eye irritation.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Aquatic Acute 1: H400 - Very toxic to aquatic life.
Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
Flam. Liq. 3: H226 - Flammable liquid and vapour.
Skin Sens. 1: H317 - May cause an allergic skin reaction.
STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

Skin Sens. 1: Calculation method
STOT SE 3: Calculation method
Flam. Liq. 2: Calculation method (2.6.4.3)
Eye Irrit. 2: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu
http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
LogPOW: Octanolwater partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier
IARC: International Agency for Research on Cancer

- CONTINUED ON NEXT PAGE -

valresa

480057 - Hazelnut Concentrated Stain 057

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -